

# 3704 AutoCoil EV Charger

## Single Pole, Dual Pole or Wall Mount

The 3704 AutoCoil EVSE with automatic cable management offers the most advanced electric vehicle charging in the market today. The unit is engineered and manufactured for ease of use by any EV customer – just plug in, charge, and after disconnecting just walk the cable back as it retracts back into the housing automatically.

The model 3704 provides 220V AC up to 30A. Designed as per the SAE J1772 requirements to meet or exceed all safety codes specified by UL and NEC, the unit is engineered for commercial interior or exterior locations and comes in single or dual wall or pole mounted versions. The 3704 meets or exceeds all NEMA 250 CLASS 3R specifications.

The 3704 is equipped with a state-of-the-art cable management system, which fully retracts and protects the 20-foot cable from harsh weather and vandals. The cable management system is ADA and OSHA compliant by keeping cables off the ground when connected to a vehicle and when not connected. There are tens of thousands of chargers today with cables on the ground in weather and in the pathway of pedestrians creating a public safety hazard. EVSE is the leader in EV charger cable management design that addresses OSHA and ADA requirements.

Modular in design, the model 3704 can be configured for simple on-off control, or the more demanding requirements of credit/debit and ID card processing. EVSE chargers are compatible with Open Charge Alliance charger networks from Greenlots and OpConnect. This ensures universal access to chargers without proprietary membership required. The Open Charge Alliance is an international standard for the development of charger networking based on an open vs proprietary architecture.

### Power Specifications

Voltage/Circuit: 208VAC - 240VAC@30A  
Input Phase: Single  
Connector: SAE J1772™ & NEC 625 Compliant  
Pilot: SAE 1772 Compliant  
Ground Fault: GFCI 20MA  
Protection: Auto Test  
Breaker Size: 40A  
Overload: 40A Trip at 30 amps  
Protection: Reclosure CCID  
Ground Wire: Continual Test

### Dimensions

Height to Lot Surface: 60" high  
Width, Single Unit: 10.78" wide  
Width, Dual Unit: 25" wide

### Environmental

Environmental: NEMA 3R  
Operation Temp: -28°C to +50° C (-20°F to 122°F)  
Humidity: 95% Non-Condensing

### Safety & Compliance

Safety Standards: UL 2231-1 & 2231-2  
UL 2594  
CAN/CSA C22.2 No. 61010-1/R: 2008  
UL 61010-1/R:2008.  
EN 61010-1:2009  
NEC 625 Compliant  
Personal Protection: UL 2231 (CCID)  
EMI: FCC Part 15 Class B

### Operating Information

Communication: Ethernet, Cellular & Other  
Radio Communications,  
Wi-Fi Compatible  
Networks: Web-Based, LAN, WAN, Cellular,  
OCPP (Open Charge Protocol)  
Power Monitoring: Integration with 3rd  
Party Monitoring Systems  
EV Charge Payment: EV Charger Kiosk or Payment  
Station Integrated with  
Current System  
Modular EVSE Payment Options  
to Adapt to Your System



AC.06.15

\* Patent Pending

## Smart Charging Solutions for Electric Vehicles

EVSE LLC - A Division of Control Module Inc.  
89 Phoenix Ave, Enfield, CT 06082  
Daniel J. Shanahan - 860.916.7162 - dshanahan@controlmod.com



Local 860.745.2433 - Toll Free 800.722.6654

www.EVSEllc.com